

GRAPHICS - INK-JET DIGITAL

 Issue date : 24/03/2016
 Date last modification : 30/04/2018

4-GL2A-09782 RI-JET DECO-WALL 100 HOP AP972 EXTRA PERMANENT WK135
Face Material

High opacity matt white monomeric vinyl film.

Type	Monomeric vinyl	
Colour and Finish	Matt white	
Weight	134 g/m ² ±10%	ISO-536
Thickness	100 μ ±10%	ISO 534-80
	1 % ±10%	

Adhesive

Extra permanent solvent based adhesive with excellent adhesion on indoor and outdoor walls.

Reference	AP927 extra permanent	
Type	Acrylic extra permanent	
Min. Appl. Temp.	+5°C	
Service Temp.	-30°C / +120°C	
Shear	Medium	
Tack	12 N/inch ²	
Final Adhesion	16 N/inch	

Liner

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	135 g/m ² ±10%	PP-032 - ISO 536
Thickness	145 μ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

For walls interior decoration.

This PVC self adhesive material offers a cost effective solution to interior designer who are looking for a film to decorate internal walls or shop interior.

We advise an overlap of 1,5 cm when positioning the decals.

Indoor durability 4 years unprinted material.

If the printing solvents aren't completely removed before installation the resultant graphic will show very high shrinkage and edge curl.

The shrinkage of the unprinted material, based on the Finat test method FTM 14, give us values <2%.

Printing Methods

Printable with eco-solvent, solvent, UV and Latex ink-jet. Print and immediate cut is feasible.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

 24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

