

POLLYTEX PES TENT FABRIC 270G FR B1

100% polyester water resistance tent fabric, woven style

APPLICATIONS:

Tents, sunbeds, advert umbrellas, roller blinds, tradeshow, outdoor events promotional

MATERIAL DETAILS:

PROPERTIES	TYPICAL VALUE	TEST METHOD
Material	100% polyester	DIN 60001, ASTM D7641
Weight	270g/sq.m; 7.9oz/sq.yd	ISO536
Thickness	360+/-30mic	ISO534
Yarn	600DX600D	DIN EN ISO 2060, ASTM D1907
Whiteness	95±10	ISO11475
Color	L*: 93±2.0 a*: 5.0±2.0 b*: -10±2.0	----
Opacity	>80%	ISO2471
Shrinkage	≤2%	200°C, 45s
Flame Resistance	B1, NFPA 701	DIN 4102-1-B1, NFPA 701 Test1
Recommend Fixation Temperature	190-200°C, 45s	---
Yellowing Temperature	≥210°C	SUPRKC REX-C400, 30s

INK SUPPORT:

Dye Transfer
✓

PRODUCTION DETAILS:

WIDTH:	1.60 /2.38/ 3.2m	Standard: DIN EN ISO 3759, ASTM D751-2006
LENGTH:	50 m	Standard: DIN EN ISO 3759, ASTM D751-2006



Ecco Plus Sp. z o.o.

ul. Sienkiewicza 1/1 lok. 102

15-092 Białystok

tel./faks 85 747 94 11

www.eccoplus.pl