

POLLYTEX PES DISPLAY SUB MATT 220 gsm

100% polyester deco display fabric, warp-knitted

Applications:

Display, Backdrops, Pop-up

Material details:

Properties	Typical Value	Test Standard
Material	100% polyester	DIN 60001, ASTM D7641
Weight	220±5%g/sq.m; 6.5±5%oz/sq.yd	ISO536
Yarn	75X40X40 denier	DIN EN 2060, ASTM D1907
Whiteness	170±10	ISO11475
Color	L*: 90±2.0 a*: 12±2.0 b*: -22±2.0	GB/T 7974-2002
Shrinkage	≤2%	200°C, 45s
Flame Resistance	B1, NFPA 701	DIN 4102-1-B1, NFPA 701 Test1
Recommend Fixation Temperature	190-200°C, 45s	
Yellowing Temperature	≥210°C	SUPRKC REX-C400, 30s
Opacity	>80%	ISO2471
Elasticity	Low Elasticity(3%-5%)	ength*Width=200*50mm, Speed=100mm/min, Tension=20N

Ink support:

Dye Direct	Dye Transfer
Yes	Yes

Production Details:

Width	Max 320 cm	Standard: DIN EN ISO 3759, ASTM D751-2006
Length	50 m	Standard: DIN EN ISO 3759, ASTM D751-2006

NOTE:

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources.
Recommended storage temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

