

POLLYTEX PES PEARL BACKLIT UV 140 gsm

100% polyester dwoven, milky backlit fabric

Applications:

LED Light Box, Frame System, Pop-up, SEG

Material details:

Properties	Typical Value	Test Standard
Material	100% polyester	DIN 60001, ASTM D7641
Weight	140g±5%/sq.m; 4.1±1.5oz/sq.yd	ISO536
Thickness	150±30	ISO534
Opacity	85-95	ISO2471
Whiteness	95±10	ISO11475
Color	L*: 94±2.0 a*: 1.0±2.0 b*: -3±2.0	
Gloss[60°]	3 - 6	
Yarn	68D*150D denier	DIN EN 2060, ASTM D1907
Flame Resistance	B1, NFPA 701	DIN 4102-1-B1, NFPA 701 Test1

Ink support:

UV
Yes

Production Details:

Width	Max 320 cm	Standard: DIN EN ISO 3759, ASTM D751-2006
Length	50 m/ 100 m	Standard: DIN EN ISO 3759, ASTM D751-2006

NOTE:

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources.
Recommended storage temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.



Ecco Plus Sp. z o.o.
ul. Sienkiewicza 1/1 lok. 102
15-092 Białystok
tel./faks 85 747 94 11
www.eccoplus.pl