

VULCANO OCTOPUS PP WHITE MATT

Vulcano Octopus is a reusable, removable, bubble-free and environmental friendly high quality printing media with octopus micro suction technology. It is ideal for short term and long term indoor application, such as sticker, promotion items, seasonal decoration, POP instructions, etc. Vulcano Octopus can be easily applied to most clean, smooth and flat surfaces.

General Information:

*250 µm white polypropylene film
Eco-solvent, UV Digital, Offset, Latex printing compatible
Matt white surface
One side self-adhesive with liner*

Feature:

*No residue
Bubble-free
Easy and quick to install
Removable, repositionable and reusable*

Advantage:

*Very easy and quick to install. Almost everyone can install this material by themselves easily. Skilled person is not required.
Very easy to stick and easy remove.*

Benefit:

*Minimum or no installation cost
Time saving
No cleaning cost*

Application:

*Sticker
Promotion items such as Posters, glass window advertising etc
Seasonal decoration
Suitable for most clean, smooth and flat surface, such as: glass, metal etc*

Print Compatibility:

Eco-solvent/ UV Digital/ Offset/ Latex

Cautions:

*Not recommended for outdoor usage
To optimize print results, printer needs to be set for highest print quality.
Avoid hand oil and dirt contaminate the backside.
Keep the film flat during application, crease and curing will affect the adhesion persistence
Due to different applying surface and environment, we cannot guarantee the material will work on every condition. Please always test on applying surface before large scale usage.*

Storage:

*Store at temperature conditions of 10 ~25 °C and 50% relative humidity.
We recommended that you always keep this product in its original packaging.*



Installation and Handling:

The application area should be clean and free of dirt.

Using water to assist applying the material is not necessary and not recommended.

Product specification:

<i>Film Thickness</i>	<i>250±15 μm</i>
<i>Total Thickness</i>	<i>300±18 μm</i>
<i>Film Weight</i>	<i>155±10 μm</i>
<i>Total Weight</i>	<i>200±12 μm</i>
<i>180°Peel Strength</i>	<i>5 ~120g/25mm</i>
<i>Release force</i>	<i><20g/25mm</i>
<i>Elongation at Break</i>	<i>>150%</i>
<i>Apperance</i>	<i>White</i>
<i>Working Temperature</i>	<i>-20 °C to 80 °C</i>
<i>Demensional Stability</i>	<i>≦0.1 inch</i>
<i>Shelf Life</i>	<i>Two years</i>

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. Therefore we can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.



Ecco Plus Sp. z o.o.
 ul. Sienkiewicza 1/1 lok. 102
 15-092 Białystok
 tel./faks 85 747 94 11
www.eccoplus.pl

The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application



Ecco Plus Sp. z o.o.
ul. Sienkiewicza 1/1 lok. 102
15-092 Białystok
tel./faks 85 747 94 11
www.eccoplus.pl