

dtec Mesh NO Liner 270gsm

<i>Item</i>	<i>Unit</i>	<i>Value</i>		<i>Test Method</i>
<i>Base Fabric</i>	<i>Denier</i>	<i>1000DX1000D</i>		<i>(High tenacity yarn) 100%PES</i>
<i>Construction</i>	<i>Weaving/inch</i>	<i>12X12</i>		<i>/</i>
<i>Weight of MESH</i>	<i>Gsm/m2</i>	<i>270 +/- 20</i>		<i>DIN53352 BS3424 Method5B</i>
<i>Weight of pvc liner</i>	<i>Gsm/m2</i>	<i>0</i>		<i>DIN53352 BS3424 Method5B</i>
<i>Total weight</i>	<i>Gsm/m2</i>	<i>270 +/- 20</i>		<i>DIN53352 BS3424 Method5A</i>
<i>Width</i>	<i>cm</i>	<i>Up to 320</i>		<i>/</i>
<i>Tensile Strength</i>	<i>N/5cm</i>	<i>Warp</i>	<i>1250</i>	<i>DIN53352 BS3424</i>
		<i>Weft</i>	<i>1100</i>	
<i>Tearing Strength</i>	<i>N</i>	<i>Warp</i>	<i>235</i>	<i>DIN53356 BS3424</i>
		<i>Weft</i>	<i>225</i>	
<i>Air permeability</i>	<i>mm/s</i>	<i>2649</i>		<i>GB/T 2410-2008</i>
<i>Light transmission</i>	<i>/</i>	<i>37%</i>		<i>GB/T 5453-1997</i>
<i>Temperature Resistance</i>	<i>°C</i>	<i>-20 ~70</i>		<i>DIN53357 BS3425 Method10</i>
<i>Lacquering</i>	<i>None</i>			
<i>Flammability</i>	<i>\</i>			
<i>LOW CADMIUM & HEAVY METALS</i>	<i>\</i>			
<i>Conclusions and Announcements</i>	<i>Declaration by GLP: Please choose GLP products suitably according to relative provisions or industrial standards. GLP bears the responsibility for the specified technical and performance data on this page only. GLP is not responsible for any other liability. (The technical data on this page is calculated on average, and ±5% tolerance is acceptable)</i>			





Ecco Plus Sp. z o.o.
*ul. Sienkiewicza 1/1 lok. 102
15-092 Białystok
tel./faks 85 747 94 11
www.eccoplus.pl*