

# DTEC BANNER PLUS FRONTLIT WHITE/BLACK

## MATT 450 gsm

coated frontlit 450gsm 1000\*1000 18\*18 black back

### MATERIAL DETAILS:

ITEM	DATA	UNIT TEST	METHOD
Fabric	High tenacity yarns 100% PES(1000D)		DIN EN ISO2060
Construction	Weaving 18*18	inch	DIN60001
Total weight	450	g/sq.m	DIN53352 BS3424 method5A
Weight of fabric	240	g/sq.m	DIN53352 BS3424 method5B
Weight of pvc coating	210	g/sq.m	DIN53352 BS3424 method5B
Tensile strength	Warp : 2300	N/5cm	DIN53354 BS3424 method6A
	Weft : 1900		
Tearing strength	Warp : 240	N	DIN53356 BS3424 method7A
	Weft : 200		
Adhesion	80	N/5cm	DIN53357 BS3425 method9B
Suitable temperature	-20 -----+70	°C	DIN 53372 BS3424 method10
Flame retardancy		No	
Lacquering		No	

The data above are on average, so there will be  $\pm 5\%$  tolerance.



Ecco Plus Sp. z o.o.  
ul. Sienkiewicza 1/1 lok. 102  
15-092 Białystok  
tel./faks 85 747 94 11  
[www.eccoplus.pl](http://www.eccoplus.pl)