

# Magneto white matt PVC (B)

magnetic foil – Magneto white matt PVC (B)

## DIMENSIONS & TOLERANCE:

ITEM	LENGTH (m)			WIDTH (mm)		THICKNESS (mm)				THICKNESS OF PVC (mm)
	20	30	15	1020	620	0,4	0,5	0,6	0,7	
Size	20	30	15	1020	620	0,4	0,5	0,6	0,7	0,1~0,13
Tolerance	0/+0.6			-1/+5	-1/+3	±0.04	±0.05			

## PULL STRENGTH:

THICKNESS (mm)	POLE PITCH (mm)	PULL (g/cm <sup>2</sup> )
0,4	2,0	≥17
0,5	2,0	≥24
0,6	2,0	≥29
0,7	2,0	≥35

## PHYSICAL DATA:

	0,4	0,5	0,6	0,7
Total thickness (mm)	0,50±0.05	0,60±0.06	0,70±0.06	0,80±0.06
Reference Weight (g/m <sup>2</sup> )	1540±154	1880±188	2180±218	2520±252
Hardness (Shore D)	45±5	45±5	45±5	45±5
Flexibility	Without cracking	Without cracking	Without cracking	Without cracking
Opacity	100%	100%	100%	100%



Ecco Plus Sp. z o.o.  
ul. Sienkiewicza 1/1 lok. 102  
15-092 Białystok  
tel./faks 85 747 94 11  
[www.eccoplus.pl](http://www.eccoplus.pl)

## **STORAGE:**

*For reference, it works within the range of - 20 °C to+70 °C of the ambient temperature, and the customer needs to test the actual application environment*

## **STORAGE CONDITION:**

*25°C and 50% humidity conditions*

## **SHELF LIFE:**

*12 months under original packaging condition The magnetic force is permanent and will not degrade in normal temperature without strong magnetic interference*



**Ecco Plus Sp. z o.o.**  
ul. Sienkiewicza 1/1 lok. 102  
15-092 Białystok  
tel./faks 85 747 94 11  
[www.eccoplus.pl](http://www.eccoplus.pl)