

PET ROLL – UP MATT 250 mic.

FEATURES:

- *perfectly absorb solvent, latex, UV curable inks with quick dry*
- *PVC free, no phthalate - eco friendly indoor / outdoor product*
- *delivers accurate colors and vivid results on its high-quality matte surface*
- *very smooth & flatness with perfect curl balance structure for roll up display*
- *99% blocking against rear lights, white backing*
- *no yellowing but, be recommed to use the laminating film for long term display*
- *back side available for Latex, UV curable printing*

APPLICATIONS:

- *poster, billboard, exhibition hall display, shop display, Subway*

MATERIAL DETAILS:

<i>PROPERTIES</i>	<i>RESULT</i>	<i>TEST METHOD</i>
<i>Total thickness</i>	<i>250±5 micron</i>	<i>ASTM D645</i>
<i>Total weight</i>	<i>240±5 g/m2</i>	<i>ASTM D646</i>
<i>Whiteness</i>	<i>95</i>	<i>ASTM D1925</i>
<i>Opacity</i>	<i>>99.9</i>	<i>ISO 2471</i>
<i>Shelf life</i>	<i>1 year</i>	
<i>Surface finish</i>	<i>semi matte</i>	
<i>Thermal property</i> <i>Heat shrinkage (dry air)</i>	<i>MD ≤1.5 %</i> <i>TD ≤0.5 %</i>	<i>Hyosung method</i> <i>(150°C x 30 min)</i>

RECOMMEND PRINTERS:

Seiko Color Painter 64S/100S, Mimaki : JV3 160/250 S/SP, Mutoh: ROCK HOOPER II, Roland: SOL-JET, DGI: MEGA-JET SIGN-JET VTIV-92/62 VTIII-98D, INFINITI: FY 6320LQ, Teck-win: TECK-JET 2500 TECK-JET 2500+ TECKPRO+3200: HP Latex L, LX series: Any UV printer



Ecco Plus Sp. z o.o.
ul. Sienkiewicza 1/1 lok. 102
15-092 Białystok
tel./faks 85 747 94 11
www.eccoplus.pl

CONDITION OF USE/ STOCKING:

All solvent materials always need to be stored in their packing and with the original protection flanges (and preferably stored vertically). In order to avoid any loss of quality, the Solvent film should also be stored in suitable conditions, that is at a temperature between 10°C and 20°C, and a relative humidity of 50%.

REMARK:

Large amounts of solvent ink on the material can activate the ink on the backside of the material.

If the material is enrolled too quickly after printing, the print on the backside of the material may become visible in your printout.

Therefore we advise you to limit the amount of ink and to leave the prints to dry sufficiently before enrolling them.



Ecco Plus Sp. z o.o.
ul. Sienkiewicza 1/1 lok. 102
15-092 Białystok
tel./faks 85 747 94 11
www.eccoplus.pl